

UPR Oil Catch Can Installation

S650 Mustang GT / Darkhorse Dual Breather Tank system

This UPR kit is designed to be used on S650 Mustangs with Hellion Turbo Sleeper system. It will work with other S650 applications where the factory air boxes have been removed.

The kit may also be used in custom applications like Coyote Swaps.

This kit **will not** fit any S650 application where the factory air boxes are in place, and will not fit with Procharger superchargers.



1. Mount the catch cans on either side of the engine compartment using the existing air box bolt as shown. The quick release knob allows easy catch can removal for servicing.



2. Most S650 Mustangs will have a plastic cover that is glued over the PCV valve on the valve cover. The PCV valve must be removed and replaced with an open fitting when using a vent to atmosphere breather tank system. To remove the PCV, use a pair of pliers and carefully twist the cover until you hear the glue crack. Remove the cover then remove the PCV valve by rotating it counterclockwise. Install the UPR open PCV fitting 5045-24 into the valve cover. Do not install any restrictors into the fitting.



3. Route the supplied hoses from each valve cover PCV fitting to the UPR Breather Tank. The short hose will connect to the driver side valve cover, the longer hose will connect to the passenger side.
4. The supplied small filter with the male quick connect fitting can be installed into the white fitting that previously connected to the air box tube.
5. The Breather tanks will connect to the valve covers only. There will be no connection to the intake manifold or air intake tube / air box. Depending on the engine configuration, you may need to cap or block off any intake manifold / supercharger vacuum port that was previously connected to the PCV.

To remove and service the catch cans, press the buttons on the fittings to release them from the catch can (NEVER pry or remove the buttons from the fittings), Unscrew the quick release mounting knob, and remove the breather tank. Unscrew the breather tank cup to dispose of the liquid. Clean the breather tank cup, tank body and filter with warm water and dish soap as needed. Harsh solvents like carb/ fuel injector cleaner or brake cleaner products are NOT recommended for cleaning. Vehicles using E85 will need to have the tanks and filters cleaned and serviced more often than vehicles using gasoline

Product Liability Statement: The purchase of the product, manufactured by UPR Products Inc. completes an agreement between UPR Products Inc. and the customer. UPR Products Inc. assumes no liability for damages or injury incurred by the buyer of this product. The buyer has complete responsibility for the installation, use and upkeep of this product

Be sure to shop our online store for the best deals: www.uprproducts.com