

UPR Trackhawk / Durango Clean Side Catch Can Installation



1. Locate the 10mm bolt holding the AC line bracket on the driver side of the front radiator support and remove it. Install the 90 degree bracket in this location with the supplied bolt (bolt may vary from picture). Be sure the short side of the 90 degree bracket is facing up.



2. Install the catch can onto the bracket with the supplied hardware. You can loosen the allen screws on the top of the catch can to allow you to turn and clock the can for the best position.





- **3.** Press the buttons on the factory fitting connected to the air box tube or cold air kit and slide it off. Connect the male UPR fitting to the factory female fitting, then connect the 45 degree fitting to the left side fitting on the catch can. Route the hose with 90 degree fittings under the cold air kit / air box tube and connect it to the male fitting on the tube. Connect other end to the catch can as shown.
- **4.** To service the catch can, unscrew the cup at the base of the can and dispose of any liquids with used drain oil according to your local regulations. Reinstall the cup by screwing it back on until it is snug. Do not overtighten the cup.

Always check and drain the catch can more often in winter / freezing weather. If the water/oil mixture in the catch can is allowed to freeze it will cause damage to the catch can and internal components. Any damage due to freezing is NOT WARRANTY. You must dispose of the liquid collected in the catch can properly (with used waste oil) properly according to your local laws.

<u>Product Liability Statement:</u> The purchase of the product, manufactured by UPR Products Inc. completes an agreement between UPR Products Inc. and the customer. UPR Products Inc. assumes no liability for damages or injury incurred by the buyer of this product. The purchaser or user of this product is responsible for the proper disposal of any hazardous materials (oil catch can contents). The buyer has complete responsibility for the installation, use and upkeep of this product.